

KD120HXE

classica Aesthetic

EAN13: 8017709257651

Subfamily: Decorative wall hood

Aesthetics: Classic

Color: Stainless steel

Hood width: 120 cm

Energy efficiency class (EEC): A+



TYPE

- Product family: Hood
- Hood width: 120 cm
- Subfamily: Decorative wall hood
- Extraction: Expulsion

AESTHETICS

- Aesthetics: Classic
- Design: Chimney
- Material: Stainless steel
- Serie: N/A
- Color: Stainless steel
- Type of steel: Brushed

CONTROLS

- Control setting: Control knobs
- Control knobs: Classic
- No. of controls: 2
- Controls colour: Steel effect

PROGRAMS / FUNCTIONS



- No. of speeds: 3

TECHNICAL FEATURES



- Light Power: 4 W
- Free outlet maximum capacity: 820 m³/h
- No. of filters: 4
- Minimum distance from ELECTRIC hob: 650 mm
- Vent outlet: 150 mm
- No. of lights: 4
- Light type: LED
- Light color temperature scale (°K): 4000 °K
- Motor power: 275 W
- Anti-grease filters: Stainless steel
- Minimum distance from GAS hob: 650 mm
- Non return valve: Yes

PERFORMANCE / ENERGY LABEL



- Grease Filtering Efficiency Class (GFEC): D
- Annual Efficiency Consumption (AEChood): 41.6 KWh/year
- Grease Filtering Efficiency (GFE): 74.9 %
- Air flow at maximum speed (Qmax): 606 m³/h
- Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 49 dB(A)
- Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 73 dB(A)
- Time increase factor (F): 0.7

- Measured air pressure at best efficiency point (Pbep): 490 Pa
- Nominal Power consumption of the light system (WL): 5 W
- Sound power level at highest setting (Lwa): 67

- Energy efficiency class (EEC): A+
- Fluid Dynamic Efficiency class (FDEC): A
- Lighting Efficiency Class (LEC): A
- Fluid Dynamic Efficiency (FDE): 36.3
- Lighting Efficiency (LE): 74.8 lux/W
- Air flow at minimum speed (Qmin): 287 m³/h
- Air flow at boost speed (Qboost): 777 m³/h
- Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A)
- Power Consumption in Off mode (Po): 0.1 W
- Power consumption in stand-by mode (Ps): 0.1 W
- Measured air flow rate at best efficiency point (Qbep): 400 m³/h
- Measured electric power input at best efficiency point (Wbep): 150 W
- Average illumination of the light on the cooking surface (Emiddle): 329 lux

dB(A)

ELECTRICAL CONNECTION

- Electrical connection rating: 179 W
- Frequency (Hz): 50-60 Hz
- Voltage: 220-240 V

SPEED 1

- Extraction rate IEC 61591: 287 m³/h
- Power: 176 W
- Noise level IEC 60704-2-13: 49 dB(A)

SPEED 2

- Extraction rate IEC 61591: 389 m³/h
- Power: 230 W
- Noise level IEC 60704-2-13: 58 dB(A)

SPEED 3

- Extraction rate IEC 61591: 606 m³/h
- Power: 260 W
- Noise level IEC 60704-2-13: 67 dB(A)

INTENSIVE SPEED

- Extraction rate (IEC 61591): 777 m³/h
- Power: 286 W
- Noise level IEC 60704-2-13: 73 dB(A)

OPTIONAL

- Round Charcoal filters (kit 2 pieces): **FLT6**

For availability in specific countries please contact your [local agent](#) .



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

