


KD120HXE

Hood, Decorative wall hood, Classica, Stainless steel, 120 cm, A+



TYPE

Hood width: 120 cm • Product family: Hood • Extraction: Extraction • EAN code: 8017709257651 • Hood Type: Decorative wall hood

AESTHETICS

Aesthetics: Classica • Design: Chimney • Type of steel: Brushed • Colour: Stainless steel • Finishing: Satin • Material: Stainless steel

CONTROLS

Control knobs: Classic • Control setting: Control knobs • No. of controls: 2 • Controls colour: Steel effect

PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

TECHNICAL FEATURES

Light color temperature scale (°K): 4000 °K • Anti-grease filters: Stainless steel • Light Power: 4 W • Minimum distance from GAS hob: 650 mm • Non return valve: Yes • No. of filters: 4 • No. of lights: 4 • Free outlet maximum capacity: 820 m³/h • Motor power: 275 W • Light type: LED • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm

PERFORMANCE / ENERGY LABEL

Air flow at minimum speed (Qmin): 287 m³/h • Average illumination of the light on the cooking surface (Emiddle): 329 lux • Power Consumption in Off mode (Po): 0.1 W • Fluid Dynamic Efficiency class (FDEC): A • Power consumption in stand-by mode (Ps): 0.1 W • Energy efficiency class (EEC): A+ • Time increase factor (F): 0.7 • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 73 dB(A) • Sound power level at highest setting (Lwa): 67 dB(A) • Air flow at maximum speed (Qmax): 606 m³/h • Measured air flow rate at best efficiency point (Qbep): 400 m³/h • Fluid Dynamic Efficiency (FDE): 36.3 • Annual Efficiency Consumption (AEHood): 41.6 kWh/a • Grease Filtering Efficiency (GFE): 74.9 % • Grease Filtering Efficiency Class (GFEC): D • Measured air pressure at best efficiency point (Pbep): 490 Pa • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A) • Nominal Power consumption of the light system (WL): 5 W • Air flow at boost speed (Qboost): 777 m³/h • Lighting Efficiency Class (LEC): A • Lighting Efficiency (LE): 74.8 lux/W • Measured electric power input at best efficiency point (Wbep): 150 W • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 49 dB(A)

ELECTRICAL CONNECTION

Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Electrical connection rating: 179 W

OPTIONAL ACCESSORIES

SPEED 1

Power: 176 W • Noise level IEC 60704-2-13: 49 dB(A) • Extraction rate IEC 61591: 287 m³/h

SPEED 2

Power: 230 W • Noise level IEC 60704-2-13: 58 dB(A) • Extraction rate IEC 61591: 389 m³/h

SPEED 3

Power: 260 W • Extraction rate IEC 61591: 606 m³/h • Noise level IEC 60704-2-13: 67 dB(A)

INTENSIVE SPEED

Extraction rate (IEC 61591): 777 m³/h • Noise level IEC 60704-2-13: 73 dB(A) • Power: 286 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 800x1200x555 • Width: 1200 mm • Depth (mm): 555 mm • Product Height (mm): 800 mm

OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

