

KFAB75CR

50's Retro style Aesthetic

EAN13: 8017709224875

Subfamily: Decorative wall hood

Aesthetics: 50's style retro

Color: Cream

Hood width: 75 cm

Energy efficiency class (EEC): A+



TYPE

- Product family: Hood
- Hood width: 75 cm
- Electronic control: Yes
- Subfamily: Decorative wall hood
- Extraction: Ricirculation

AESTHETICS

- Aesthetics: 50's style retro
- Design: Angled
- Material: Painted material
- Serie: N/A
- Color: Cream
- Type of steel: Brushed

CONTROLS

- Control setting: Electronic buttons
- Led color: White

PROGRAMS / FUNCTIONS



- No. of speeds: 3

TECHNICAL FEATURES



- Light Power: 1 W
- Free outlet maximum capacity: 820 m³/h
- No. of filters: 3
- Charcoal filters included: Yes
- Minimum distance from ELECTRIC hob: 650 mm
- Vent outlet: 150 mm
- No. of lights: 2
- Light type: LED
- Light color temperature scale (°K): 4000 °K
- Motor power: 280 W
- Anti-grease filters: Stainless steel
- Filter replacement indicator: Yes
- Minimum distance from GAS hob: 650 mm
- Non return valve: Yes

PERFORMANCE / ENERGY LABEL



- Grease Filtering Efficiency Class (GFEC): E
- Annual Efficiency Consumption (AEChood): 36 KWh/year
- Grease Filtering Efficiency (GFE): 61.1 %
- Air flow at maximum speed (Qmax): 649 m³/h
- Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 50 dB(A)
- Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A)
- Time increase factor (F): 0.49
- Measured air pressure at best efficiency point (Pbep): 422 Pa
- Nominal Power consumption of the light system (WL): 2 W
- Energy efficiency class (EEC): A+
- Fluid Dynamic Efficiency class (FDEC): A
- Lighting Efficiency Class (LEC): A
- Fluid Dynamic Efficiency (FDE): 36.6
- Lighting Efficiency (LE): 68.2 lux/W
- Air flow at minimum speed (Qmin): 333 m³/h
- Air flow at boost speed (Qboost): 797 m³/h
- Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A)
- Power consumption in stand-by mode (Ps): 0.7 W
- Energy Efficiency Index: 39.7
- Measured air flow rate at best efficiency point (Qbep): 421 m³/h
- Measured electric power input at best efficiency point (Wbep): 135 W
- Average illumination of the light on the cooking surface (Emiddle): 150 lux

- Sound power level at highest setting (Lwa): 67 dB(A)

ELECTRICAL CONNECTION

- Electrical connection rating: 282 W
- Voltage: 220-240 V
- Current: 1 A
- Frequency (Hz): 50-60 Hz

SPEED 1

- Extraction rate IEC 61591: 333 m³/h
- Power: 198 W
- Noise level IEC 60704-2-13: 50 dB(A)

SPEED 2

- Extraction rate IEC 61591: 477 m³/h
- Power: 246 W
- Noise level IEC 60704-2-13: 59 dB(A)

SPEED 3

- Extraction rate IEC 61591: 649 m³/h
- Power: 286 W
- Noise level IEC 60704-2-13: 67 dB(A)

INTENSIVE SPEED

- Extraction rate (IEC 61591): 797 m³/h
- Power: 294 W
- Noise level IEC 60704-2-13: 72 dB(A)

ACCESSORIES INCLUDED

- Remote control: Yes
- Sliding door: Yes

OPTIONAL

- **FLTSI**
- **KITCMNFABCR**

VERSIONS

- KFAB75WH: White
- KFAB75RD: Red
- KFAB75BL: Black

For availability in specific countries please contact your [local agent](#) .



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

