

KPF9OR

Product family: Hood
Subfamily: Decorative wall hood
Aesthetics: Portofino
Design: Chimney
Width category: 90cm
Extraction: Expulsion
Material: Stainless Steel + Painted Material
Color: Orange
Type of steel: Brushed
EAN code: 8017709236328
Hood width: 90 cm



Aesthetics

Serigraphy colour: Black
 Logo: Applied

Controls

Control setting: Control knobs
 No. of controls: 2
 Control knobs: Portofino
 Controls colour: Steel effect

Programs / Functions

No. of speeds: 3
 Intensive speed

Technical Features

No. of lights: 2
 Light type: LED
 Light Power: 2 W
 Light color temperature scale (°K): 4000 °K
 Free outlet maximum capacity: 815 m³/h
 Motor power: 275 W
 No. of filters: 3
 Anti-grease filters: Stainless steel

Vent outlet: 150 mm
 Minimum distance from ELECTRIC hob: 650 mm
 Minimum distance from GAS hob: 750 mm
 Non return valve

| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dB(A)] |
|-----------------|-------------------------------------|---------------------------------------|
| Speed 1 | 288 | 48 |
| Speed 2 | 421 | 63 |
| Speed 3 | 630 | 67 |
| Intensive speed | 781 | 72 |

Performance / Energy Label



Annual Efficiency Consumption (AEChood): 40.1 KWh/year
Energy efficiency class (EEC): A+
Fluid Dynamic Efficiency (FDE): 36.2
Fluid Dynamic Efficiency class (FDEC): A
Lighting Efficiency (LE): 78.2
Lighting Efficiency Class (LEC): A
Grease Filtering Efficiency (GFE): 78.2 %
Grease Filtering Efficiency Class (GFEC): C
Air flow at minimum speed (Qmin): 288 m³/h
Air flow at maximum speed (Qmax): 630 m³/h
Air flow at boost speed (Qboost): 781 m³/h
Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 48 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A)

Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A)
Time increase factor (F): 1.00
Energy Efficiency Index per first cavity: 40.3
Measured air flow rate at best efficiency point (Qbep): 413 m³/h
Measured air pressure at best efficiency point (Qbep): 476 Pa
Measured electric power input at best efficiency point (Wbep): 151 W
Normal Power of the light system (WI): 2 W
Average illumination of the light on the cooking surface (Emiddle): 172
Sound power level at highest setting (Lwa): 67 dB(A)

Electrical Connection

Electrical connection rating: 277 W
Voltage: 220-240 V
Frequency (Hz): 50-60 Hz
Power supply cable length: 1000 mm

Also available

Alternative colours available: White, Black, Stainless steel, Anthracite, Yellow, Green, Red
Available colours:
KPF9WH-KPF9BL-KPF9X-KPF9AN-KPF9YW-KP9OG-KPF9RD

Accessories not included



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

