

# KT90PE

Victoria Aesthetic

EAN13: 8017709211677

Subfamily: Decorative wall hood

Aesthetics: Victoria

Color: Cream

Hood width: 90 cm

Energy efficiency class (EEC): A



## TYPE

- Product family: Hood
- Hood width: 90 cm
- Subfamily: Decorative wall hood
- Extraction: Expulsion

## AESTHETICS

- Aesthetics: Victoria
- Design: Chimney
- Material: Painted material
- Serie: N/A
- Color: Cream
- Type of steel: Brushed

## CONTROLS

- Control setting: Control knobs
- Control knobs: Victoria
- No. of controls: 2
- Controls colour: Steel effect

## PROGRAMS / FUNCTIONS



- No. of speeds: 3

## TECHNICAL FEATURES



- Light Power: 1 W
- Free outlet maximum capacity: 820 m<sup>3</sup>/h
- No. of filters: 3
- Minimum distance from ELECTRIC hob: 650 mm
- Vent outlet: 150 mm
- No. of lights: 2
- Light type: LED
- Light color temperature scale (°K): 3000 °K
- Motor power: 275 W
- Anti-grease filters: Aluminium
- Minimum distance from GAS hob: 750 mm
- Non return valve: Yes

## PERFORMANCE / ENERGY LABEL



- Grease Filtering Efficiency Class (GFEC): C
- Annual Efficiency Consumption (AEChood): 59.4 KWh/year
- Grease Filtering Efficiency (GFE): 76.6 %
- Air flow at maximum speed (Q<sub>max</sub>): 567 m<sup>3</sup>/h
- Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>): 49 dB(A)
- Airborne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>): 69 dB(A)
- Measured air flow rate at best efficiency point (Q<sub>bep</sub>): 438 m<sup>3</sup>/h
- Measured electric power input at best efficiency point (W<sub>bep</sub>): 176 W
- Average illumination of the light on the cooking surface (E<sub>middle</sub>): 225 lux
- Energy efficiency class (EEC): A
- Fluid Dynamic Efficiency class (FDEC): A
- Lighting Efficiency Class (LEC): A
- Fluid Dynamic Efficiency (FDE): 30
- Lighting Efficiency (LE): 102.3 lux/W
- Air flow at minimum speed (Q<sub>min</sub>): 334 m<sup>3</sup>/h
- Air flow at boost speed (Q<sub>boost</sub>): 788 m<sup>3</sup>/h
- Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>): 61 dB(A)
- Energy Efficiency Index: 52.4
- Time increase factor (F): 1.00
- Measured air pressure at best efficiency point (P<sub>bep</sub>): 434 Pa
- Nominal Power consumption of the light system (WL): 2 W
- Sound power level at highest setting (L<sub>wa</sub>): 61 dB(A)

## ELECTRICAL CONNECTION

---

- Electrical connection rating: 278 W
- Frequency (Hz): 50-60 Hz
- Voltage: 220-240 V

## SPEED 1

---

- Extraction rate IEC 61591: 334 m<sup>3</sup>/h
- Power: 199 W
- Noise level IEC 60704-2-13: 49 dB(A)

## SPEED 2

---

- Extraction rate IEC 61591: 439 m<sup>3</sup>/h
- Power: 231 W
- Noise level IEC 60704-2-13: 57 dB(A)

## SPEED 3

---

- Extraction rate IEC 61591: 567 m<sup>3</sup>/h
- Power: 260 W
- Noise level IEC 60704-2-13: 61 dB(A)

## INTENSIVE SPEED

---

- Extraction rate (IEC 61591): 788 m<sup>3</sup>/h
- Power: 280 W
- Noise level IEC 60704-2-13: 69 dB(A)

## OPTIONAL

---

- Round Charcoal filters (kit 2 pieces): **FLT6**
- **KITCMNKPU**

## VERSIONS

---

- KT90BE: White
- KTR90XE: Stainless steel
- KT90BLE: Black

For availability in specific countries please contact your [local agent](#) .



**A**

A: Product drying performance, measured from A+++ to D / G depending on the product family



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

