

# KPF9AN

**Product family:** Hood  
**Subfamily:** Decorative wall hood  
**Aesthetics:** Portofino  
**Design:** Chimney  
**Width category:** 90cm  
**Extraction:** Expulsion  
**Material:** Stainless Steel + Painted Material  
**Color:** Anthracite  
**Type of steel:** Brushed  
**EAN code:** 8017709236366  
**Hood width:** 90 cm



## Aesthetics

---

Serigraphy colour: Silver  
 Logo: Applied

## Controls

---

Control setting: Control knobs  
 No. of controls: 2  
 Control knobs: Portofino  
 Controls colour: Steel effect

## Programs / Functions

---

No. of speeds: 3  
 Intensive speed

## Technical Features

---

No. of lights: 2  
 Light type: LED  
 Light Power: 2 W  
 Light color temperature scale (°K): 4000 °K  
 Free outlet maximum capacity: 815 m<sup>3</sup>/h  
 Motor power: 275 W  
 No. of filters: 3  
 Anti-grease filters: Stainless steel

Vent outlet: 150 mm  
 Minimum distance from ELECTRIC hob: 650 mm  
 Minimum distance from GAS hob: 750 mm  
 Non return valve

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	288	48
Speed 2	421	63
Speed 3	630	67
Intensive speed	781	72

## Performance / Energy Label

---



Annual Efficiency Consumption (AEChood): 40.1 KWh/year  
Energy efficiency class (EEC): A+  
Fluid Dynamic Efficiency (FDE): 36.2  
Fluid Dynamic Efficiency class (FDEC): A  
Lighting Efficiency (LE): 78.2  
Lighting Efficiency Class (LEC): A  
Grease Filtering Efficiency (GFE): 78.5 %  
Grease Filtering Efficiency Class (GFEC): C  
Air flow at minimum speed (Qmin): 288 m<sup>3</sup>/h  
Air flow at maximum speed (Qmax): 630 m<sup>3</sup>/h  
Air flow at boost speed (Qboost): 781 m<sup>3</sup>/h  
Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 48 dB(A)  
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A)

Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A)  
Time increase factor (F): 1.00  
Energy Efficiency Index per first cavity: 40.3  
Measured air flow rate at best efficiency point (Qbep): 413 m<sup>3</sup>/h  
Measured air pressure at best efficiency point (Qbep): 476 Pa  
Measured electric power input at best efficiency point (Wbep): 151 W  
Normal Power of the light system (WI): 2 W  
Average illumination of the light on the cooking surface (Emiddle): 172  
Sound power level at highest setting (Lwa): 67 dB(A)

### Electrical Connection

---

Electrical connection rating: 277 W  
Voltage: 220-240 V  
Frequency (Hz): 50-60 Hz  
Power supply cable length: 1000 mm

### Also available

---

Alternative colours available: White, Black, Stainless steel, Yellow, Green, Red, Orange  
Available colours:  
KPF9WH-KPF9BL-KPF9X-KP9YW-KPF9OG-KPF9RD-KPF9OR

### Accessories not included

---



#### FLT6

Round Charcoal filters (kit 2 pieces)



#### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

